



**STOVING PROTECTIVE COATINGS .**

-----

Stoving Protective Coating is based on special type of Modified acrylic resin. It has Bright and High gloss finish with good scratch resistance and marproof finish.

Description : Low backing SPC is available in different Vibrant colors as well as in clear coat also.

Application : To be applied by spraying at 30 to 40 viscosity  
: in Fordcup no.4 at 30 degree centigrade using  
: our special SGST Thinner.

Surface Preparation/Procedure: The surface should be cleaned and free from Dust,  
: grease and loose or flecked of paint particles.  
: Then as desired the clear lacquer to be applied  
: by spraying at desirable consistency.

Stoving Schedule : 80 to 120 degree C for 10 to 20 minutes.

Covering Capacity : 25-30 sq.mtr/ltr per coat at 25 microns DFT.

Available Colors : Green, Yellow, Red, Orange ,Violet,Burgandy,  
: Blue, Brown, Black, and Orange & Clear.

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND  
CUSTOMER IS ADVISED TO TEST THE MATERIAL BEFORE USE

KIRAN PAINTS PVT. LTD.

Factory : Plot No. 48, M.I.D.C., Taloja Ind. Area, Dist. Raigad, Maharashtra-410208, INDIA.

Fact. Tel.: 91-22-27410100 Fax: 91-22-27410101 Mobile: 9320724330

Email : [info@kiranpaints.com](mailto:info@kiranpaints.com)

Website : [www.kiranpaints.com](http://www.kiranpaints.com)