



"Kiriprotect" Heavy duty Chlorinated Rubber based Paint.

These paints are specially manufactured with special grade of Chlorinated rubber and plastified with unsaponifiable matter to withstand resistance to acid and alkalis and all corrosive gases and host of many chemicals.

TECHNICAL DETAILS :

Consistency : Smooth and uniform.

Mode of packing : Single Pack.

Color : As required .

Weight per liter : 0.95 +/- 0.05 kg. (depending on color)

Flash Point : 23 degree Cent.

Finish : Smooth & uniform.

Resistance of water : Excellent.

Resistance to alkali : Excellent.

Resistance to mineral acids : Good.

Resistance to organic acids : Good.

Resistance to solvents : Poor.

Resistance to corrosion : Excellent.

Film thickness : 20 microns DFT/Coat.

No of coats recommended : 2 coats.

Curing Time : Minimum 48 hrs.

Can Stability : One year from date of manufacture.

Remarks : These are the ideal paints where
Protection is required from the
Chemical except for solvents.

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND
CUSTOMER IS ADVISED TO TEST THE MATERIAL BEFORE USE

KIRAN PAINTS PVT. LTD.

Factory : Plot No. 48, M.I.D.C., Taloja Ind. Area, Dist. Raigad, Maharashtra-410208, INDIA.

Fact. Tel.: 91-22-27410100 Fax: 91-22-27410101 Mobile: 9320724330

Email : info@kiranpaints.com

Website : www.kiranpaints.com