



**EPOXY SUB FILLER**

KIRAN EPOXY SUB FILLER is a two component Epoxy Solventless filler putty, specially developed for wet surfaces and can be applied even Under water. Very useful in the repair of minor cracks underwater in different types of surfaces, hence useful in many marine applications.

When fully cured it forms an extremely tough & abrasion resistant finish. Suitable for various surfaces like metals, plastic, concrete, wood etc..

**Physical Properties**

Type:	Two packs cold cured.
Mixing Ratio :	Resin 3 : 1 Hardener
Pot life:	10- 15 mins max. To be used immediately as the pot life varies with different temperatures
Drying Period:	3-4 hours
Full Curing Time:	7 days.
Application:	By Hand or any other convenient method
Recommended DFT:	3 to 4 mm
Thinner:	Not to be added
Color/Finish:	Black, Grey / Matt

**Application Method**

Mix the base and hardener as per the recommended ratio. Mix thoroughly to attain homogeneity. Remove any loose particles on the surface and clean the surface with brush. Apply the mixture uniformly over the surface by pressing with hand. Do not add any thinner.

**THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH  
CUSTOMER IS ADVISED TO TEST THE MATERIAL BEFORE USE**

KIRAN PAINTS PVT. LTD.

Factory : Plot No. 48, M.I.D.C., Taloja Ind. Area, Dist. Raigad, Maharashtra-410208, INDIA.

Fact. Tel.: 91-22-27410100 Fax: 91-22-27410101 Mobile: 9320724330

Email : [info@kiranpaints.com](mailto:info@kiranpaints.com)

Website : [www.kiranpaints.com](http://www.kiranpaints.com)