



SILICON / ACRYLIC HR COATING

Single pack special formulated Silicon / Acrylic coatings are used in areas where heat Resistance is required along with whether and moisture. It is suitable for use on stacks, ducting & piping etc have operation temperature up to 250°C to 600°C

Type: Single Pack.

Composition: Silicon/ Acrylic Coating medium suitable pigmented.

Method of Application: Brush/Roller/Air spray/Conventional spray.

Recommended DFT : 25 Microns.

Theoretical Spreading Rate: 8 Sq.mtr/lt.

Drying Time: Touch Dry - 25 Mts.
Dry to Handle - 3 hrs.
Hard Dry - 18 hrs.

Color: White/Grey/Aluminum/Black/Red oxide

Finish: Glossy/Semi Glossy/Matt.

Thinner: HR Thinner.

Storage Life: Nine Months as long as the sealed containers are
: Kept under cover, in dry place and under normal
: Temperature condition.

THE ABOVE INFORMATION IS GIVEN IN GOOD FAITH AND
CUSTOMER IS ADVISED TO TEST THE MATERIAL BEFORE USE

KIRAN PAINTS PVT. LTD.
Factory : Plot No. 48, M.I.D.C., Taloja Ind. Area, Dist. Raigad, Maharashtra-410208, INDIA.
Fact. Tel.: 91-22-27410100 Fax: 91-22-27410101 Mobile: 9320724330
Email : info@kiranpaints.com
Website : www.kiranpaints.com